

Shunt trip release MX, ComPacT NSX, 125VDC, screwless spring terminal connections

LV429393

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ComPacT	
Range of Product	ComPact NSX100250	
	ComPacT NSX100250	
	ComPact NSX400630	
	ComPacT NSX400630	
	ComPact NSX100250 DC	
	ComPacT NSX100250 DC	
	ComPact NSX100250 DC PV	
	ComPacT NSX100250 DC PV	
	ComPact NSX400630 DC	
	ComPacT NSX400630 DC	
	ComPact NSX400630 DC PV	
	ComPacT NSX400630 DC PV	
Device short name	MX	
Product or Component Type	Voltage release	
Device Application	Control	
Voltage release type	Opening coil	
	Shunt trip release	
[Uc] control circuit voltage	125 V DC	
Range compatibility	ComPacT ComPacT NSX	
	ComPacT ComPacT NSX DC	
	ComPact ComPact NSX	
	ComPact ComPact NSX DC	
	EasyPact EasyPact CVS	
	PowerPact PowerPact Multistandard	

Complementary

Operating threshold	0.71.1 x Un opening	
Response time	50 ms	
Control signal type	Maintained Impulse	
Impulse duration	>= 20 ms	
Supply inrush power	10 W	
Auxiliary connection terminal	spring 0.00080.002 in² (0.51.5 mm²) AWG 20AWG 16)	
Wire stripping length	0.3 in (7 mm)	

Ordering and shipping details

Category	US10NET01081
Discount Schedule	0NET
GTIN	3606480019159

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	No	
Country of origin	Pl	

Packing Units

r adming dimes	
Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.77 in (4.500 cm)
Package 1 Width	1.85 in (4.700 cm)
Package 1 Length	2.44 in (6.200 cm)
Package weight(Lbs)	4.148 oz (117.600 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	2.87 in (7.300 cm)
Package 2 Width	4.13 in (10.500 cm)
Package 2 Length	9.25 in (23.500 cm)
Package 2 Weight	2.707 lb(US) (1.228 kg)
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	11.81 in (30.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	16.438 lb(US) (7.456 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	81ad7b79-ef4f-4746-bccc-1c5b358db33b
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes
Silicon free	No

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.