

# Specifications

Photo is representative

## Eaton DILM9-10(24V60HZ)

Eaton XT IEC mini contactor, 9A, 24 Vac, 60 Hz, 1NO, 9A, Frame B, 45 mm, 60 Hz, 0.5, 1.5/ 3, 3, 5, 7.5 (1/3PH @120, 240/208, 240, 480, 575 V), Three-pole, Screw terminals, Full voltage non-reversing miniature contactor, 4 kW

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC mini contactor
<b>CATALOG NUMBER</b>	DILM9-10(24V60HZ)
<b>EAN</b>	4015082766818
<b>PRODUCT LENGTH/DEPTH</b>	2 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	3 in
<b>PRODUCT WEIGHT</b>	0.3 lb
<b>WARRANTY</b>	1 year
<b>COMPLIANCES</b>	RoHS Compliant CE Marked
<b>CERTIFICATIONS</b>	EN 60947 UL Listed IEC 60947 CSA Certified
<b>CATALOG NOTES</b>	Screw terminals (6-65A), 5 mm (80-150A), no lugs (185-2000A)

## Product specifications

AMPERAGE RATING	9A
HP RATING - MAX	0.5, 1.5/ 3, 3, 5, 7.5 (1/3PH @120,240/208,240,480,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing miniature contactor
FREQUENCY RATING	60 Hz
FRAME SIZE	45 mm
TERMINALS	Screw terminals
COIL	24 Vac 60 Hz
COIL VOLTAGE	24 Vac, 60 Hz
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	9 A
SERIES	XT IEC
OPERATION	Non-reversing
POWER CONSUMPTION	4 kW

## Resources

	<a href="#">Contactors Explained</a>
MULTIMEDIA	<a href="#">S1. E4. Ask the Experts - NEMA, IEC and DP contactors</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - DILM9-10(24V60HZ)</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

