

# Specifications



Photo is representative



## Eaton LS-11

Eaton LS-Titan Miniature DIN Limit Switch, Top Push Plunger, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 1NO-1NC, Slow Make Before Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Cage Clamp,  $\pm 0.02\text{mm}$  accuracy

### General specifications

PRODUCT NAME	Eaton LS-Titan miniature DIN limit switch
CATALOG NUMBER	LS-11
UPC	786685514178
PRODUCT LENGTH/DEPTH	1.22 in
PRODUCT HEIGHT	2.99 in
PRODUCT WIDTH	1.32 in
PRODUCT WEIGHT	0.1188 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Listed

## Product specifications

TYPE	LS-Titan
CONTACT RATING	6A at 240Vac, 3A at 24Vdc
ACCURACY	±0.02mm
ENCLOSURE MATERIAL	Polyamide PA66-GF25
CONNECTION	Cage clamps
CONTACT CONFIGURATION	1 NO-1 NC, slow make before break, positive opening
SWITCH TYPE	Top push plunger
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	IP66, IP67
MAXIMUM AC CURRENT	6 A
MAXIMUM DC CURRENT	3 A

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - LS-11](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

