

New Telemecanique LC1-D32-10 (LC1D3210) Contactor Replacement - Data Sheet for US Breaker Brand Contactors with the Trusted UL Certification!




NC1 D32 10

- ✓ Standards: UL508, CSA C22.2, IEC 60947, and CE Marked
- ✓ Integral DIN Rail & Base Mounting in One Compact Footprint
- ✓ Superior ISO Quality Proven by Multiple Global Standard Certifications

Telemecanique LC1D3210 Contactor Replacement Cross Reference

US Breaker- Brand Part #	Telemecanique Contactor Cross Ref Direct	Telemecanique Contactor Cross Ref Direct	Control Coil Voltage	Auxiliaries NO NC	Price Each
NC1 D32 10 - V24	LC1D3210 - B7	LC1-D32-10 - B7	24V B7	1 1	\$38.71
NC1 D32 10 - V120	LC1D3210 - G6	LC1-D32-10 - G6	120V G6	1 1	\$38.71
NC1 D32 10 - V240	LC1D3210 - U6	LC1-D32-10 - U6	240V U6	1 1	\$38.71

NC1 D32 Contactor Technical Data



NC1D Type	NC1-D32
Thermal Current Ith (AC-1 IEC) Amps	660V 50
Inductive Current (AC-3 IEC) Amps	380/400V 32
UL Power Rating 3 Phase (Hp)	240V 15 460V 20 600V 20
UL Power Rating 1 Phase (Hp)	120V 3 240V 5
IEC Power Rating (KW)	380/400V 15
Operations (AC-3)	Elec. 800,000 Mech. 8,000,000

NC1 D32 Contactor Dimensions (in.)

Dim (in)	H	W	D	Daux	a	b	Ø
NC1 D32 10	3.4	2.2	3.9	5.5	1.6	1.9	0.18

NC1 D32 Contactor Coil Data

NC1D Type	NC1-D32
Coil Power	Start-up (VA) 110 Holding (VA) 11
Operation Range of Rated Voltage	Pick-up Voltage 85% - 100% Drop-out Voltage 20% - 75%

Accessories for NC1 D32 10 Contactors



NC1F411



NC1F422



NCF111C



NCSR2A



NC1F5



NC1MI0932a

Auxiliary Contacts

US Breaker- Part #	Telemecanique Cross Ref
NC F4 20	LA1DN 20
NC F4 11	LA1DN 11
NC F4 02	LA1DN 02
NC F4 40	LA1DN 40
NC F4 31	LA1DN 31
NC F4 04	LA1DN 04
NC F4 22	LA1DN 22
NCF1 11C	LA8DN 11

Time Delay Blocks

US Breaker- Part #	Telemecanique Cross Ref
NC F5 T2	LA2DT2
NC F5 D2	LA3DR2

Mechanical Interlocks

US Breaker- Part #	Telemecanique Cross Ref
NC MI 09 32a	LA9D9978

- Telemecanique part numbers are provided to assist in product selection. Proper engineering evaluation is required for each customer application.
- NC accessories are intended and UL listed for use with their associated NC1D & series F NC2 contactors