



**U.S. TOYO
FAN CORP.**

USTF75B30 Series

DC Brushless Blower

3651 Walnut Ave., Chino, CA 91710
Web: USToyoFan.com Email: Service@USToyoFan.com Phone: (909) 627-8178

USTF75B30 Series

Size: 2.98 in sq. x 1.18 in. thk
(75.7mm sq. x 30mm thk.)

Airflow: 9.0 - 11.3 CFM

Acoustical Noise: 32 - 38 dB (A)

MATERIAL: Frame - Black PBT (UL 94V-0)
Bearings - Ball
Impeller - Black PBT (UL 94V-0)

WEIGHT: 3.17 oz. (90g)

TERMINATION: Lead Wires (UL 1007, AWG24)

OPERATION TEMPERATURE: -10° to +70° C

INSULATION RESISTANCE: 10 megohms min @ 500 VDC


DIELECTRIC STRENGTH: 500 VAC for 1 min.

INSULATION: Class A

SAFETY: Impedance & Polarity Protected


SAFETY APPROVALS: UL, CSA & CE

OPERATING VOLTAGE: 12 VDC (10 to 13.8) - 24 VDC (14 TO 27.6)



PERFORMANCE CURVES: (Obtained with test chamber and methods in accordance with AMCA Std. 210-74)

USTF75B30XXHW & MW



SPECIFICATIONS: (All values are typical)

*Amps values shown are typical running. Fan labels show higher max values

PART NUMBER	VOLTS	WATTS	AMPS*	RPM	NOISE dB (A) @ 1M	CFM
USTF75B3012HW	12VDC	2.64	0.22	2900	38.0	11.3
USTF75B3012MW	12VDC	1.56	0.13	2350	32.0	9.0
USTF75B3024HW	24VDC	2.88	0.12	2900	38.0	11.3
USTF75B3024MW	24VDC	1.68	0.07	2350	32.0	9.0

MODELS AVAILABLE ON REQUEST:

Failure Detector - rotation sensing - Add Suffix "SR" to part number
Speed Controller - tach output - Add Suffix "SF" to part number